




北川鉄工所 油圧チャック用

HJ硬爪



■ 材質：SNCM21
■ 硬度：HRC58~60



単位：mm

硬爪型式	希望小売価格 (1set3個入/円・税別)	H-1	H-2	H-3	H-4	H-5	H-6	H-7	H-8	H-9	H-10	H-11	H-12	参考図	質量 (kg)
HJ05	43,200	53	23	28	10	4	30.5	14	22.5	10	M8	6	-	Fig.2	0.40
HJ06	44,600	67	31	36	12	5	39	20	28	12	M10	11	-	Fig.2	0.95
HJ08	53,600	86	35	51	14	5	31	25	18	12	M12	13.5	13.5	Fig.1	1.95
HJ10	67,500	100	40	54	16	5	43	30	17	13	M12	15	15	Fig.1	2.90
HJ12A-18	76,600	103	50	52	18	5	62	30	41	17	M14	32	-	Fig.2	3.98
HJ12A-21	98,900				21						M16				3.90
HJ15-22	157,300	143	62	86	22	8	55	43	38	20	M20	40	40	Fig.1	9.60
HJ15-25.5	157,300				25.5										5
HJ21	222,600	159	80	90	25	9	104	50	55	40	M20	55	55	Fig.3	14.50




※硬爪兼用表は119ページを参照ください。

北川鉄工所 油圧チャック用

Tナット(ジョーナット)



■ 材質：SCM440 ■ 硬度：HRC38



単位：mm

Tナット型式	希望小売価格 (1set3個入/円・税別)	A	B	C	D	E	F	G	H	参考図	ボルト 形式
T05	9,500	10	-	14	M8	9.5	5.5	14.5	15	Fig.1	CBK204
T-B-05	11,700	10	-	18	M8	10	5.5	14	15.5	Fig.1	CBKB05
T-HJ-5	11,700	10	-	19	M8	12.5	5.5	15	18	Fig.1	-
T06	8,900	12	-	20	M10	11	7.5	17.5	18.5	Fig.1	CBK206
TB06	8,900	12	-	20	M10	15	7.5	17.5	22.5	Fig.1	CBK206
T08	10,200	14	-	25	M12	12	8.5	20.5	20.5	Fig.1	CBK208
TB08	10,200	14	-	25	M12	16	9.5	20.5	25.5	Fig.1	CBKH08
T10	11,600	16	-	30	M12	13	8.5	22.5	21.5	Fig.1	CBK208
TB10	11,600	16	-	30	M12	16	9.5	22.5	25.5	Fig.1	CBKH08
T12	15,600	21	-	30	M16	16.25	11.5	29.5	27.8	Fig.1	CBK212
TB12	15,600	18	-	30	M14	20	13.5	26.5	33.5	Fig.1	CBKH12
T-HJ-12	19,400	18	-	38	M14	20	13.5	26.5	33.5	Fig.1	CBK012
T15	31,800	24	22	43	M20	29	16.5	33.5	45.5	Fig.2	CBKB15
TB15	31,800	25.5	-	26	M20	20.25	19	35	39.25	Fig.3	CBKN15
T-KN15	29,000	25.5	-	43	M20	20.25	19	35	39.25	Fig.1	CBKN15
T-HJ-18*	38,700	25	-	60	M20	35	19	37.5	54	Fig.1	CBKJ18
T21	36,000	25	-	27	M20	26	19	37.5	45	Fig.3	CBKN21
T-HJ-24*	48,400	25	-	80	M20	35	19	40	54	Fig.1	CBKJ24

*受注生産品です。

※Tナット兼用表は119ページを参照ください。