




北川鉄工所 油圧チャック用

HJ



爪形状



取付ボルト穴寸法

インチ	穴径(mm)
4	13.5
5	13.5
6	17
8	HJ8-H120:20 その他:19
10	HJ10-H120:20 その他:19
12	23
15	32
24	32

単位：mm

生爪型式	希望小売価格 (1set3個入/円・税別)	A	B	C	D	E	F	G	H	K	セレーション ピッチ	爪形状	質量 (kg)		
HJ	4	H25	4,400	55	23	25	10	4	31	14	M8	3	1.5	C	0.60
		H40	5,600			40									0.90
	5	H27	4,400	62	23	27	10	4	33	19	M8	11	1.5	B	0.60
		H40	5,600			40									0.90
	6	H36	5,100	75	32	36	12	6	40	20	M10	-	3.0	A	1.40
		H60	9,200			60									2.40
		H90*	13,300			90			36						4.20
	8	H42	5,900	95	35	42	14	6	46	25	M12	-	3.0	A	2.60
		H60	10,300			60									3.70
		H80	13,300			80									5.10
		H100	16,500			100			6.40						
	10	H120*	19,400	90	36	120	16	6	45	30	M12	-	3.0	A	7.80
		H42	7,000			42			3.60						
		H60	11,100			60			5.20						
		H80	16,100			80			7.10						
	12	H100	19,900	110	40	100	18	6	59	38	M14	-	3.0	A	8.60
		H120	24,200			120									10.70
		H48	12,700			48									5.80
H80		20,500	80			9.40									
15	H100	27,600	129	48	100	22	9	60	60	M20	-	3.0	A	11.80	
	H70*	30,300			70									13.30	
18	北川「N-21」をご使用ください(97ページ掲載)														
21	北川「N-21」をご使用ください(97ページ掲載)														
24	H90*	108,900	210	74	90	25	9	90	80	M20	-	3.0	A	29.10	

*受注生産品です。

*生爪兼用表は119ページを参照ください。